

PRINTERS & PEOPLE YOU CAN TRUST

500, 1000 3ROW PRINTERS



WHITE, CMYK, AND VARNISH - ALL IN ONE PASS.



48" X 96" MEDIA AREA

60" X 120" MEDIA AREA

PRINTER HIGHLIGHTS

- > Printer is designed to print varnish perfectly
- > Separate rows for white and varnish printheads
- > White and Varnish can print simultaneously
- > Embossing capabilities for enhanced output

RICOH GEN6 PRINTHEAD

Nozzle quantity: 1280

Pico-liter: Variable 5-10-15 pl

Effective Print Width: 54.1 mm

Max Operating Frequency: 30 Khz

3ROW FEATURES & BENEFITS

SIMPLE, SAFE AND EFFECTIVE USE FOR VARNISH PRINTING.

Simple file preparation for flood coat and spot varnish applications.

HIGH SPEED VARNISH PRINTING.

In line varnish supports bi-directional printing, increases the efficiency up to 4 times com-pared to similar solutions.

SEPARATE VARNISH LED CURING LAMPS.

Separate varnish curing lamps protect from led light flashing of printheads.

CET COLOR VARNISH PRINTING WORKFLOW

VARNISH CAN BE ADDED WITH THE CONTROL SOFTWARE



WHITE & VARNISH PRINTING CAN BE PRINTED SIMULTANEOUSLY BY CHOOSING W-CMYK-V MODE & PRINT



NO NEED FOR SEPARATE VARNISH APPLICATION OR LAMP ADJUSTMENTS

VARNISH MAKES A BIG DIFFERENCE FOR YOUR PRINTING

- OGLOSSY FINISH ENHANCES YOUR IMAGE TO CREATE A VIVID, SHARP RESULT.
- LONG LASTING PRESERVES YOUR COLOR AND KEEPS PRINTS BRIGHT AS NEW.
- EMBOSSING SIMULATE AN EMBOSSING TECHNIQUE THAT STIMULATES TOUCH.



SPECIFICATIONS

MODEL		500	1000
PRINTHEAD		Ricoh Gen6	Ricoh Gen6
QUANTITY OF PRINTHEADS		4-9 Three Row	4-9 Three Row
	2 pass	433	485
	6 pass	158	178
MAX PRINT SPEED	9 pass	107	120
	12 pass	80	91
	24 pass	39	45
MAX RESOLUTION	1440 X 1200 dpi		
PRINT MODE	Unidirectional and bidirectional		
MAX PRINT AREA	48" x 96"		60" x 120"
MAX MEDIA THICKNESS	4 inches		
MEDIA TYPE	Rigid and flexible flat materials		
INK	Environmentally friendly LED curable ink (VOC free)		
INK COLOR	CMYK + Lc + Lm + W + V		
MACHINE SIZE (L X W X H)	184" x 99" x 55"		206" x 107" x 55"
MACHINE NET Weight	2536		3197
SHIPPING WEIGHT	3848		4762
POWER SUPPLY	220 - 230 VAC. 60Hz 30 AMP (single phase)		
RIP SUPPORT	Onyx		
UV CURING	LED		
ENVIRONMENT	Separated workroom in good cleaning and ventilated condition, avoid direct sunlight Temperature: 64°F - 86°F (18° C – 30° C) Constant Humidity: 45%-70%		

3ROW



ABOUT CET COLOR





WE GO ABOVE & BEYOND FOR OUR CUSTOMERS

At CET Color, our customers are family and our number one priority. We go the extra mile to ensure that we are available to assist you with all of your printing needs.



EXPERIENCE

We draw on years of experience in the printing industry to create state-of-the-art machines and offer unparalleled service.



WIDE VARIETY OF READILY AVAILABLE PRODUCTS

Our Atlanta facility is stocked with a large inventory of printers, parts, inks and other consumable items that are ready to be shipped.



TRAINING

At CET, we provide unique and meticulous training to both our technicians and your operators because we believe that it is an integral part of owning one of our printers.



QUALITY PRINTERS & PRODUCTS YOU CAN TRUST

CET Color Printers are highly engineered with long life and ease of use in mind. Our team is here to assist you from beginning to end of your printer life.

4450 Commerce Dr. SE

Atlanta, GA 30336







